

# **Conterra SYNERGY**



### Announcing: Brand new for 2021.

Brand new design specifically engineered for light sand and synthetic arena footing additives. Special footing materials take specialized equipment to maintaitn, and that's why the experts at Conterra set out to build a solution specific to this market.

## **Ride Hard ... Stay Grounded!**

Affordable - Effective - Efficient Arena and Track Grooming Maintenance

### **Conterra SYNERGY**

#### **Features**

- The Conterra Synergy Groomer is designed for use on light sand and synthetic footings.
- The Conterra Synergy Groomer is designed to be pulled with an ATV, UTV, Garden or Compact Tractor.
- Two rows of flex tines designed to mix your surface, followed by an open cage roller to secure your footing.
- The Rear Open Cage Roller is split into two sections to enhance footing stabilization and reduce roller-skid around corners.
- The Conterra Synergy features two of Conterra's Revolutionary Depth Control Systems. One is the Tine Adjustment Jack, which allows you to easily and quickly adjust your surface mix, and extend the life of your tines. The Second is the Transport Lift Jack which allows you to lift the entire groomer of the ground and transport across your yard riding on the tires.
- Arena Tines are easily replaced by removing a bolt and retainer clip.
- Frame is constructed from laser cut 1/4" steel plate and 2"x2" square tube cross braces for years of dependable service.
- The No Scuff Wall Wheel helps the operator navigate the arena and can be mounted at the front or rear on either side.
- Wide Floatation Tires are mounted on 1000lb axles with Easy-Lube hubs to ensure a long life and smooth ride.
- The Conterra Synergy is available in size widths of 64" and 76".
- Black Powder Coat finish.
- The Conterra Synergy ships assembled and ready to use when it reaches your door.







Wall Wheel to help navigate your arena. Mount on left or right - front or back.



Tires are located inside the frame for optimal grooming coverage.



Depth Gauge to monitor tine settings.